

DuraFrame® High Strength Coated Recycled Board

Reliability. It's that simple.®

Qualities:

- 100% recycled
- Constructed of strong fibers for increased tear, tensile and stiffness properties
- Bright, double clay-coated surface, ideal for eye-catching graphics
- Water resistant to retain strength and form under the most rigorous conditions
- Meets Immersion, Cobb and Water Drop specifications for demanding conditions

Environmental attributes of RockTenn CRB:

- 100% recycled fiber with an average of 35% post-consumer content
- Requires 70% less total energy and 90% less water to produce when compared to similar substrates
- CRB is recyclable* – and is the most recovered packaging material in the U.S.

*Packaging may not be recyclable in your area.

Typical Properties

Caliper	.022	.024	.026	.028
Nominal Basis Weight	86	93	100	107
Taber Stiffness				
MD	390	525	635	750
CD	195	255	300	350
Tear				
MD	520	570	620	700
CD	560	600	650	730
Sheffield Smoothness	140	150	150	150

The information provided here identifies the target value for each product. The actual value of the characteristics may vary slightly from one run to another. This information is subject to change without notice.

DuraFrame High Strength CRB is produced at our Stroudsburg Mill located in Delaware Water Gap, PA, and at our Dallas Mill in Dallas, TX.



Contact Us:

www.rocktenn.com
877.643.5414