

DuraTote® High Strength Coated Recycled Board

Reliability. It's that simple.®

Qualities:

- 100% recycled
- Smooth, clay-coated surface for eye-catching graphics
- 2:1 stiffness ratio for stacking strength and panel integrity for all packaging sizes
- Outstanding freeze-thaw performance
- Meets Immersion, Cobb and Water Drop specifications for demanding conditions
- FDA-compliant for contact with most dry, fatty and aqueous foods

Environmental attributes of RockTenn CRB:

- 100% recycled fiber with an average of 35% post-consumer content
- Requires 70% less total energy and 90% less water to produce when compared to similar substrates
- CRB is recyclable* – and is the most recovered packaging material in the U.S.

*Packaging may not be recyclable in your area.

Typical Properties

Caliper	.016	.018	.020	.022	.024	.026	.028	.030	.032	.034
Nominal Basis Weight	68	74	80	86	93	100	107	114	122	130
Taber Stiffness										
MD	180	245	320	390	525	635	750	825	925	1125
CD	90	130	155	195	255	300	350	410	450	500
Tear										
MD	375	430	450	520	570	620	700	720	770	820
CD	440	465	490	560	600	650	730	780	830	884
Sheffield Smoothness	100	120	140	140	150	150	150	160	160	160

The information provided here identifies the target value for each product. The actual value of the characteristics may vary slightly from one run to another. This information is subject to change without notice.

DuraTote High Strength CRB is produced at our Stroudsburg Mill, located in Delaware Water Gap, PA.



Contact Us:

www.rocktenn.com
877.643.5414